This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problems Mailbox.





PCT/GB 0 0 / 0 1 2 0 4 **09 / 937767**

INVESTOR IN PEOPLE

The Patent Office Concept House Cardiff Road Newport South Wales NP10 800

REC'D **24 MAY 2000**WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

subjects the company to certain additional company law rules.

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

Signed

Andrew Gersey

Dated

27 April 2000

An Executive Agency of the Department of Trade and Industry

Patents Form 1/77

Patents Act 1977 (Rule 16)



2984R99 E435995-1 C21514___ P 00 0.00 - 9907059.1

29 MAR 1999

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form) 9907059.1

The Patent Office

Cardiff Road Newport Gwent NP9 1RH

1. Your reference

SMART

SPANNER

- 2. Patent application number (The Patent Office will fill in this part)
- 3. Full name, address and postcode of the or of each applicant (underline all surnames)

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

MICE ALEXANDER BUCHAMAN, BESCHTROE COTTACE, MEN GILSTON BY LEVEN FIFE

KY85TF 06511760001

4. Title of the invention

SMARE SPANNER

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

MIGEL BUCHAVAN,
BEZHTREE COTIAGE,
NOW CILLETON,
By LEVEN, FIFE

MURGITROYD & COMPANY 373 SCOTLAND STREET GLASGOW G5 8QA. F51/77 10/4/00

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number Country

Priority application number (if you know it)

Date of filing
(day / month / year)

1)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

n/A

- 8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:
 - a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body. See note (d))

10

Patents Form 1/77 9. Enter the number of shee any of the following items you are file, with this form. Do not count copies of the same document Continuation sheets of this form - Déscription Claim(s) Abstract 4444 Drawing(s) 10. If you are also filing any of the following, state how many against each item. Priority documents Translations of priority documents Statement of inventorship and right to grant of a patent (Patents Form 7/77) Request for preliminary examination and search (Patents Form 9/77) Request for substantive examination (Patents Form 10/77) Any other documents (please specify) 11. In request the grant of a patent on the basis of this application.

person to contact in the United Kingdom

12. Name and daytime telephone number of

Warning
After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

OR

Signature

01592

0133484 0381

775010

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Date 26,

SMART SPANNER

This invention relates to a Smart Spanner.

Ring Spanners are well known, they are used for the tightening or slackening of known screw nuts or bolts. In use the hexagonal flats and corners on the inner side of the Spanner Ring grip the hexagonal flats and corners of the screw nuts or bolts to be tightened or slackened such that when the spanner shaft is rotated in the appropriate direction the screw nut or bolt is slackened or tightened as required. However if the screw nut or bolt is undersized, damaged or worn, it is very likely that the ring spanner will 'slip' instead of properly gripping or engaging the flats and corners of the screw nuts or bolts to be tightened or slackened.

According to the present invention there is provided a Smart Spanner comprising of a novel ring spanner whereas the inner area of the spanner ring can be substantially reduced during use to enhance the gripping action of the inner Smart Spanner ring on normal, undersized, damaged or worn screw nuts or bolts. Providing there is sufficient initial grip the more torque applied to the Smart Spanner Ring the more the inner area of the Smart Spanner Ring reduces, further enhancing the Smart Spanner Ring's grip on the known screw or nut to be turned, greatly reducing the opportunity of Spanner 'slip' occuring and the subsequent screw nut or bolt damage or the failure of the Spanner to tighten or slacken the screw nut or bolt to be turned.

A special embodiment of the invention will now be described by way of example with reference to the accompanying drawings which:-

- Figure 1 Illustrates in perspective the Smart Spanner gripping a screw nut whereas torque is being applied in the correct direction whereby the ramp cam, pin or roller is acting on the decreasing ramp incorporated in the end segment of the Smart Spanner Ring thereby closing the Smart Spanner Ring.
- Figure 1a Shows in perspective the worn screw nut gripped by the inner

 Smart Spanner Ring in figure 1.
- Figure 2 Illustrates in front elevation the Smart Spanner Ring with no torque applied showing the convex curves of the inner Smart Spanner Ring relieved at the corners by smooth curves. The end segment of the Spanner Ring incorporating a decreasing ramp opposite a ramp cam protruding from the Spanner shaft.
- Shows in front elevation the Smart Spanner as in Fig 2 whereas
 the end segment of the Smart Spanner Ring incorporates a
 catch to prevent the Spanner Ring being damaged by operation
 in the wrong direction.
- Figure 2b Shows in end elevation the Smart Spanner as in Fig-2a.
- Figure 3 Shows in front elevation the Smart Spanner whereas the

 Smart Spanner Ring is partially hinged. The partially hinged

 Smart Spanner Ring is shown in differing positions of

 open-ness.

Figure 4 Illustrates in front elevation the Smart Spanner whereas the Smart Spanner Ring is hinged at more than one corner of the inner Smart Spanner Ring.

Figure 4a Shows in front elevation the Smart Spanner as in Fig 4 whereas the Smart Spanner Ring is shown in an open position.

Figure 4b Shows in side elevation the Smart Spanner as in Fig 4a.

Referring to the drawings the Smart Spanner (1) comprises of a shaft (2) with a Smart Spanner Ring (3) at either one or both ends. The Smart Spanner Ring end segment (3a) incorporates a decreasing ramp (3b) opposite the ramp cam, pin or roller (4) attached to the shaft (2) with a preferable ring stop (7). The preferably hexagonal inner ring (3h) of the Smart Spanner (1) consists of convex curves (3d) relieved at their corners (3c) by smooth curves. In a further example of the Smart Spanner (1) the Smart Spanner Ring end segment (3a) further incorporates a safety catch (3f) to prevent damage to the Smart Spanner Ring (3) if the Smart Spanner (1) is operated in the wrong direction.

A preferable operating direction indicator (5) is shown on the shaft (2).

A further example of the Smart Spanner Ring (3) is shown whereas one or more of the corners (3c) of the hexagonal inner ring (3h) consists of known swivels or hinges (3g) between the Smart Spanner Ring segments (3e).

Any known screw nut or bolt depicted is numbered (6) and hexagonal flats numbered (6a).

In use the Smart Spanner (1) engages the known screw nut or bolt (6) to be tightened or slackened via its inner hexagonal ring (3h) as the Smart Spanner (1) is operated in the correct direction as indicated by the preferable direction indicator (5) providing there is sufficient initial grip, part of the torque applied to the shaft (2) is transmitted inwardly by the ramp cam, pin or roller (4) onto the decreasing ramp (3b) incorporated into the end segment (3a) of the Smart Spanner Ring (3) the Smart Spanner Ring (3) end segment (3a) is propelled inwards by the force applied to the decreasing ramp (3b) by the ramp cam, pin or rollers (4) towards the ring stop (7).


The inner hexagonal shape of the inner Spanner ring (3h) is shaped to relieve the stresses within the Spanner Ring (3) material as the Spanner Ring (3) deforms inwards the corners (3c) of the inner hexagonal Spanner Ring (3h) are relieved by smooth curves and the 'flats' of the inner hexagonal Spanner Ring (3h) consist of convex curves (3d) which contact the known screw, nut or bolts (6) hexagonal flats (6a) at approximately the mid points of these flats (6a). If the known screw, nut or bolt (6) is damaged or worn, providing there is sufficient hexagonal flat (6a) or flats (6a) available to enable the Smart Spanner hexagonal inner ring (3h) to engage and grip the known screw nut or bolt (6), the Smart Spanner Ring (3) will deform inwards to provide further grip enabling further torque to be used to turn the known screw, nut or bolt (6).


between the shaft (2) and Spanner Ring (3) such that the Spanner Ring (3) can swivel open to allow a known tube or pipe to pass into the Smart Spanner hexagonal inner ring (3h). When the hinged section (3g) of the Spanner ring (3) is closed and the decreasing ramp (3b) is engaged against the ramp cam, pin or roller (4) the Smart Spanner (1) can be used to tighten or slacken appropriately sized known pipe nuts. The Smart Spanner (1) can be removed by reversing this procedure.

Alternatively each corner (3c) of the Smart Spanner Ring (3) can consist of swivels or hinges (3g) allowing a greater range of hexagonal or other shapes to be engaged and especially a known screw, nut or bolt (6) where it is difficult to engage the Smart Spanner (1) in a normal manner.

Abstract

A Smart Spanner (1) consisting of an inwardly deformable Spanner Ring (3) whereas when torque is applied to the Smart Spanner shaft (2) in the correct direction the hexagonal inner spanner ring (3h), which consists of inward convex curves (3d) relieved at their corners (3c) by smooth curves, grips the hexagonal flats (6a) of the operated known screw nut or bolt (6) via approximately the mid point of a their hexagonal flats (6a). Providing there is sufficient initial grip, the inner Spanner Ring (3h) will deform closing inwards greatly increasing its grip on the flats (6a) of the known screw nut or bolt (6) as the decreasing ramp (3b) on the Spanner Ring end segment (3a) is forced inwards by the inwardly directed force acting through the curved cam (4) protruding from the Spanner shaft (2) as the Spanner shaft (2) has torque applied in the appropriate direction thus enabling greater torque to be used to turn damaged, worn or undersized screw nuts or bolts (6).





ထူလူ 3_b

FIGURE 3

FIGURE 40 120 36% FIGURE 46 *M*. 3 haure 4c

Par[GB00/01204 14/4/00 Murgitroya € Co 9907059.1